

**NEW**

**CURTIS DYNA-FOG®** Ltd

"Innovators of Spraying and Fogging Technology Since 1947"

**For Professional Use**

**SUPERHAWK™ XP**

**SUPERHAWK™ XP**

*Portable Thermal Fogger  
Petroleum-Based  
Pulse-Jet Powered*

**Huge Fog Output...  
Ultra-Light-Weight...  
Compact Size...**



**Fast . . . Easy  
Starting Every Time!**

Compact, ultra-light-weight and powerful, the addition of the **Superhawk XP** to the **Superhawk** product line offers yet another option for Public Health officials and other industry professionals. Powered by the same reliable Dyna-Fog® stainless steel engine, the **Superhawk** remains the machine of choice by Health Ministry professionals, Mosquito Control Departments, Pest Control operators and others. It's ultra-light-weight design and ability to produce large volumes of dense fog make the **Superhawk** ideal for use in both local and remote areas. Built to rigid quality standards and backed by more than 65 years in the industry, the **Superhawk** continues to be an essential part of any program where performance, simplicity and reliability are required.



**PROUDLY MADE  
IN THE USA**



Scan image for  
more information

**Contact Us For Your Nearest Distributor:**  
**Ph: +1.317.896.2561 email: info@dynafog.com**

SPECIFICATIONS:	SUPERHAWK XP
Performance Of Combustion Engine:	22 KW., 18,900 KCal/hr., 30 HP.
Solution Output:	0-42 L/hr. 0-11 U.S. Gal/hr. Produces 76,000 cubic feet (2200 cubic meters) of effective output per minute
Flow Control:	Interchangeable Orifice, Metering Valve (Optional)
Solution Tank Capacity:	4.5 liters (1.2 gallons)
Solution Tank Construction:	High Density Polyethylene (HDPE Plastic)
Solution Tank Pressure:	0.28 Bar. (4 PSI.)
Gasoline Tank Capacity:	1.1 liters (0.3 gallons)
Gasoline Tank Construction:	High Density Polyethylene (HDPE Plastic)
Gasoline Tank Pressure:	Vented, Non-Pressurized
Gasoline Consumption:	1.9 L/hr. (0.5 Gal/hr.)
Ignition Source:	"Buzzer" coil
Battery:	1.5 VDC: (1) 1.5 V "AAA" Size
Fog Particle Size:	0.5 - 50 Microns (VMD.)
Weight (Empty):	6.4 kilograms (14.1 pounds)
Dimensions (cm): Dimensions (inches):	132 X 24 X 36 (L X W X H) 52 X 9 X 14 (L X W X H)
Shipping Size (cm): Shipping Size (inches):	140 X 28 X 41 (L X W X H) 55 X 11 X 16 (L X W X H)
Shipping Weight:	13.2 kilograms, 29 pounds
Shipping Volume:	.16 cubic meters, 5.6 cubic feet
Options:	Metering valve flow control, 12 VDC. High Voltage Ignition
Sewer and leak detection attachment available	

**LIMITED 2-YEAR WARRANTY**

© 2012 Curtis Dyna-Fog, Ltd. All rights reserved. Superhawk™ is a trademark of Curtis Dyna-Fog Ltd. Dyna-Fog is a registered trademark of Curtis Dyna-Fog Ltd. To maintain the highest quality products, Curtis Dyna-Fog, Ltd. reserves the right to make any technical modifications at any time without prior notice. **MADE IN THE USA**

**www.dynafog.com**